



SMOKE ABSORBER (ASE-7011)

FEATURES

1. An efficient and powerful fan provides better performance on smoke absorption at low noise.
2. Filtration is accomplished with an activated carbon impregnated urethane foam filter and can be easily replaced.
3. Highly recommended to the factory without exhaust equipment, the product lines, and the laboratories where the procedures of desoldering are needed.
4. Free to set at anywhere, free to adjust to absorb fume sources in any direction.
5. High quality, high capability, but inexpensive price.
6. ESD stands for Anti-Static.

MANUAL INSTRUCTIONS

1. Fix the supporter.
2. Slide the activated carbon filter in the position.
3. Plug power cord in the proper source.
4. Set the switch on, this is on the left lower part.
5. Adjust the direction of absorption to fume source.

SPECIFICATIONS

Model No.	ASE-7011
AC Input	110-120V AC 60Hz
Dimensions	200mm(L) * 208mm(W) * 130mm(D) 7.9''(L) x 8.2''(W) x 5.1''(D) inches
Weight	1100g / 2.4 pounds
Packing	12 pcs
CUFT	2.8'

REPLACEMENT PART

Part No.	ASE-7011-H1
Name / Specification	FILTER SET (3 pcs per set)
Dimensions	123mm x 130mm / 4.8'' x 5.1'' inches